## Gusher® 10



### **Robust Design Stands Up To The Toughest Marine Conditions**

- Top performance
  - 65 ltrs (17 US gals) per minute
- Mounting options On Deck / Bulkhead, Thru deck
- Designed for simple installation and maintenance
- Efficiency Large non-choke valves
- · Ideal for workboats, cruisers, offshore racing
- Easy pump action Self priming
- Typical uses
  - Bilge pump out / holding tank pump out

#### **5 Year Warranty**

#### **Awards and Accreditations**

Suitable as a primary bilge pump on boats equal to or greater than 12m (40ft) in accordance with ISO15083


#### **COMPLETE YOUR SYSTEM**

Whale high quality bilge accessories including non-return valves, elbows and Y pieces see page 48 - 51



Gusher 10 Mk3 Standard BP3708

Gusher 10 Mk3 Thru Deck/Bulkhead BP3740



# Front View Side View

Side View

## **Product Information**

Model Specifications			
Model	On Deck / Bulkhead	Thru Deck / Bulkhead	
Product Code	BP3708	BP3740	
Weight	2.3 kg (5 lbs)		
Hose Connections	38 mm (11/2") Smooth Hose Connections		
Materials	Pump Body: Marine Grade LM6 Aluminium Alloy (epoxy coated) Diaphragm: Neoprene (Nitrile® option available) Fasteners: Stainless Steel		
Materials Contact With Fluid	Marine Grade LM6 Aluminium Alloy (Epoxy Coated) Neoprene, Nitrile®, Stainless Steel		
Service Kits	AK3706 - Neoprene Parts AK3714 - Nitrile® Parts for Oil and Diesel Contains: Diaphragm, Valves, Seals		
Accessories	DP3804 - Alloy Deck Plate DP8904 - Plastic Deck Plate Lid AS4405 - Spare Handle		
Maximum Suction Lift	4 m (13.5 ft)		
Maximum Discharge Head	4 m (13.5 ft)		

	BP3708 / BP3740	BP3708 / BP3740
Suction Lift	1 m (3 ft)	2 m (6 ft)
Discharge Head	0.5 m (1.5 ft)	0.5 m (1.5 ft)
45 Strokes per Minute	41 ltrs (11 US gals)	41 ltrs (11 US gals)
70 Strokes per Minute	65 ltrs (17 US gals)	65 ltrs (17 US gals)

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support.

