

**DÉFENSE
CYLINDRIQUE**

Pression :
de 300 mb (4.35 psi)
à 450 mb (6.5 psi)

C52
H. 500 mm
ø 220 mm
1.64' / 0.72'



C73
H. 700 mm
ø 250 mm
2.29' / 0.82'



C84
H. 800 mm
ø 300 mm
2.52' / 0.98'



C104
H. 1000 mm
ø 340 mm
3.28' / 1.12'



C124
H. 1200 mm
ø 360 mm
3.93' / 1.18'



C145
H. 1400 mm
ø 490 mm
4.59' / 1.51'



C175
H. 1700 mm
ø 560 mm
5.58' / 1.84'



**DÉFENSE
SPHÉRIQUE**

Pression :
de 300 mb (4.35 psi)
à 350 mb (5 psi)

/

/

/

/

S60
ø 430 mm



S70
ø 500 mm



S80
ø 560 mm



**DIMENSION
DE BATEAU**

de 23 à 30 pieds
de 7 à 9 mètres



de 30 à 43 pieds
de 9 à 13 mètres



de 43 à 52 pieds
de 13 à 16 mètres



de 52 à 62 pieds
de 16 à 19 mètres



de 62 à 98 pieds
de 19 à 30 mètres



de 98 à 131 pieds
de 30 à 40 mètres



de 131 à 180 pieds
de 40 à 55 mètres



**NOMBRE DE
DÉFENSES
CONSEILLÉ**



X6



X8



X8



X10



X12



X2



X14



X2



X16



X2

**DÉFENSE
TUBULAIRE**

Pression :
de 300 mb (4.35 psi)
à 450 mb (6.5 psi)

T52
H. 500 mm
l. 222 mm
ép. 108 mm



T73
H. 700 mm
l. 252 mm
ép. 123 mm



T84
H. 800 mm
l. 302 mm
ép. 148 mm



T104
H. 1000 mm
l. 342 mm
ép. 168 mm



T124
H. 1200 mm
l. 362 mm
ép. 178 mm



T145
H. 1400 mm
l. 492 mm
ép. 243 mm



/